

FIELD APPLIED MIN. 3/4 IN (19.1mm)
DEEP INJECTED SEALANT BAND AND CORNER
BEAD ALONG SIDE OF DSM AS SHOWN – BOTH SIDES
(SIKASIL WS-295 SILICONE SUPPLIED BY EMSEAL)

SIKALASTIC DECKPRO
TOP COAT

SIKALASTIC DECKPRO
BASE COAT

SIKASIL WS-295 "DECK GREY"
WATERTIGHT FACTORY APPLIED
TRAFFIC-GRADE SILICONE BELLOWS
(NUMBER OF BELLOWS VARIES WITH
NOMINAL MATERIAL SIZE)

1/4 IN
[6.4mm]

DSM SYSTEM
BY EMSEAL
DEPTH VARIES WITH
NOMINAL MATERIAL SIZE

EPOXY ADHESIVE
BOTH SIDES
(SUPPLIED BY EMSEAL)

IMPREGNATED EXPANDING FOAM
ANCHORING SYSTEM AND
SHOCK/SOUND ATTENUATING BAFFLE

VARIES

MOVEMENT: ±50% (TOTAL 100%) OF NOMINAL MATERIAL SIZE



A SIKA COMPANY

BUILDING TRUST



EMSEAL/SIKA SOLE SOURCE

DSM – DECK TO DECK – TYPICAL – WITH SIKALASTIC DECKPRO

THIS DOCUMENT CONTAINS INFORMATION OF A CONFIDENTIAL NATURE AND IS PROPRIETARY TO EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED USE WILL BE PROSECUTED. THIS DRAWING IS PROTECTED BY COPYRIGHT, THE RIGHT TO REPRODUCE IN ANY FORM BEING THE EXCLUSIVE RIGHT OF EMSEAL JOINT SYSTEMS LTD. ANY UNAUTHORIZED REPRODUCTION WHETHER IN TWO OR THREE DIMENSIONS WILL BE PROSECUTED. © 2014 EMSEAL JOINT SYSTEMS LTD.

DRAWN BY: PMG	DATE: 2019/03/06	SCALE: N.T.S.	SHEET No: 1 OF 1
------------------	---------------------	------------------	---------------------

PART NUMBER:

SES-001